



More information on the website
radwag.com/en/info,w1,1ZS

AP-12.5Y Automatic Device for Multichannel Pipette Calibration



The drawings, photos and graphics used are for illustrative purposes only.

Functions



Autotest



Statistics



IR sensors



GLP Procedures



Pipettes Calibration



Air density correction



Ambient conditions monitoring



Statistical Quality Control



ALIBI Memory

Datasheet

Metrological parameters	
Maximum capacity [Max]	52 g
Readability [d]	0.01 mg
Tare range	-52 g
Standard repeatability [5% Max]	5 µg
Standard repeatability [Max]	10 µg
Standard minimum weight (USP)	10 mg
Standard minimum weight (U=1%, k=2)	1 mg

Metrological parameters	
Linearity	±0.03 mg
Stabilization time	4 s
Adjustment	internal (automatic)
Typical measurement time for a 12-channel pipette with constant volume, according to ISO 8655 (for d=10 µg)*	Ponížej 20 minut
Typical measurement time for a 12-channel pipette with variable volume, according to ISO 8655 (for d=10µg)*	Ponížej 60 minut
Relative humidity	20% ÷ 80%
Physical parameters	
Display	10" touchscreen
Weighing pan dimensions	ø26 + automat
Packaging dimensions	605×560×775 mm
Net weight	17 kg
Gross weight	30 kg
Communication interface	
Communication interface	USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Environmental conditions	
Operating temperature	+10 – +40 °C
Operating temperature change rate	±0.3°C/1h (±1°C/8h)
Relative humidity change rate	±1%/h (±4%/8h)

*Depends on room conditions and user competence.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories

Antivibration Tables
 Additional modules
 Automatic Variable-Volume Pipettes
 Protective cover for balances
 Barcode scanners
 USB Hubs
 THBR 2.0 System - Ambient Conditions Monitoring

RS 232, RS 485 cables
 Balance Storage Case
 Receipt Printer
 Fingerprint Reader
 Adapters for Pipettes Calibration
 RS 232 – USB Converter

Software

- RAD Key [WX-010-0005]
- R-Lab [WX-010-0080]
- RADWAG Development Studio [WX-010-0104]

- RADWAG Remote Desktop [WX-010-0107]
- Scale Editor 2.1 [WX-010-0173]

Device dimensions

