




General Specifications:

- The scissor lift is designed for lifting purposes only.
- · Lifting with single acting hydraulic cylinder.
- Hydraulic Cylinders will be manufactured from honed pipes and chrome-plated shafts.
- Hose burst valve that prevents the platform from free falling in the event of a hose burst.
- Scissors made of st-52 quality material.
- Connection Pins manufactured from chrome-plated shaft.
- Steel construction designed and manufactured according to load distribution.
- · Original package hydraulic circuit.
- Bronze coated bushings on moving parts.
- Lubrication-free bearing rollers.
- · With safety frame.
- Maintenance safety bar for service.
- Our products are CE certified according to EN 1570 standards.
- The platform is designed to work on smooth and solid ground.

Technical Specifications	
Model	SBU
Capacity	1000 kg
Platform size (LxW)	1450x1140 mm
Closed height (C)	90 mm
Strock (H)	710 mm
Max. height (C+H)	800 mm
Lifting time	18 sn.
Motor	0,75 kW 380 V AC
Control voltage	24V DC
Control	1 Pc, With Up / Down / Emergengy Stop Buttons
Weight	Approx. 350 kg
Color	RAL 1028 - Yellow
Hydrolic power unit	External connected with 5m cable & hose
Platform top plate	Plane
Scale capacity	Max. 1000 kg
Readability	0.2 / 0.5 kg
Indicator	Depending customer specification



(Properties are subject to change without notification 01-03 / 2022)





- ♥ Tuzla Kimya Sanayicileri O.S.B Organik Cad. No:31 34953 Tuzla, Istanbul - Turkey
- **८** +90 216 593 26 30 **♣** +90 216 593 26 38