# **BU Pallet Scale**

# Mobile, fast and easy weighing





TER YAR. MAD. SAN

URUN

aN

( |

#### **Ergonomic Design**

- Easy portability with lightweigh and integrated wheels
- Optional battery operation
- Depending on industrial environment, static painted, galvanised or stainless steel construction
- Optionally use in hazardous areas

#### Accurate and Reliable Weighing

- IP67 protected, OIML approved and high quality load cells
- Shock resistant robust construction
- Standard 1500kg & 3000kg capacities with 1260 x 1000 mm size

#### Functionality

- Functional use such as labelling, formulation, and filling control with mobile weighing electronics.
- Advanced or simple weighing applications; Labelling, formulation, piece counting, filling, formulation, classifying, checking or process integrations



BAYKON BU pallet scales provides easy loading and fast weighing with portable construction. It's practical and accurate weighing for loads with pallets. It is designed to supply accurate and reliable weighing for years in any kind of industrial environments.

BAYKON BU pallet scales are compatible with OIML standards and it is produced according to European directives up to 2 x 3000d multi range accuracy classes.


BAYKON BU pallet scales are used in food, cosmetic, metal and metallurgy, logistic, chemical and in all industries at goods receiving and shipping, manufacturing, packaging application areas.



anga ng sa sa sa	
Inchnical	<b>Specifications</b>
IGUIIIUa	operindations

Models		Weighing Capacities					
		1500 kg	3000 kg				
BU 1500		•					
BU 3000			•				
Reada	ability						
OIML Approved	Single range	500 g	1 kg				
	2 x 3000e Multi range	200 / 500 g	500 g / 1 kg				
Non-approved industrial usage		100 g	200 g				
Meas	urement limits						
Minimum weighing range		10 kg	20 kg				
Repeatability		0,15 kg	0,30 kg				
Zeroing range		+ / - 30 kg	+ / - 60 kg				
Taring range		From 0 kg to maximum capacity					
Overload limit (Static)		1800 kg	3200 kg				
Const	ruction						
Fork h	eight	85	85 mm				
Numb	er of load cells		4				
Materi	al	Standard static painted, optionally galvanised or stainless steel					
Protec	tion class	IP65 / IP67 (optional) / IP68 (optional)					
Holdin	g handle and wheels	Standard					
Indica	itor						
Specif	ications	All BAYKON indicators or terminals can be connected. Please refer to the brochure of the weighing instrument for detailed information.					

### Sizes(mm)



	Α	В	С	D	E	F	Н
BU	1062	600	840	1255±5	120	140	85
BU IBC	955	600	1040	1200±5	220	220	80

## **Options**



Washable stainless steel construction



Transport wheels, indicator column and battery



Peripheral and wireless communication



Data collection software





- ♀ Kimya Sanayicileri 0.S.B Organik Cad. No:31 Tepeoren 34956 Tuzla / Istanbul / Türkiye
  ↓ +90 216 593 26 30
  ▲ +90 216 593 26 38