



More information on the website
radwag.com/en/info,w1,FGD

HRP 1000.5Y.KB Mass Comparator



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

Metrological parameters	
E1	-
E2	-
F1	-
F2	-
M1	1000 kg
M2	200 kg ÷ 1000 kg
Maximum capacity [Max]	1050 kg
Readability [d]	10 g
Standard repeatability [5% Max]	6 g
Standard repeatability [Max]	10 g
Permissible repeatability	15 g
Eccentricity (tested load)	1d / 5 mm
Electric compensation range	0 ÷ 1050 kg
Stabilization time	10 s
Adjustment	internal (automatic)

Physical parameters	
Display	10" touchscreen
Weighing pan dimensions	1000×800 mm
Controlling device dimensions	249×170×72 mm
Comparator packaging dimensions without self-centering weighing pan	1200×1000×440 mm
Net weight	121 kg
Gross weight	161 kg
Recommended load speed	0,3 m/min
Maximum permissible load speed	0,6 m/min
Weighing unit dimensions without self-centering weighing pan	1010×800×182 mm

Communication interface	
Communication interface	USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot

Environmental conditions	
Operating temperature	+15 ÷ +30 °C
Operating temperature change rate	±2°C/12h
Relative humidity	40% ÷ 60%
Relative humidity change rate	±10%/4h

Repeatability is expressed as a standard deviation determined for 6 ABBA cycles. Standard deviation is experimentally determined under ambient conditions for calibration of F2 class mass standards specified in OIML R111 (Table C.1.) document.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories

Barcode scanners
 Protective cover for balances
 THBR 2.0 System - Ambient Conditions Monitoring

Receipt Printer
 Fingerprint Reader

Software

RAD-KEY
 THB-R

RMCS System

Device dimensions



Type	A1	A2	H
HRP 200.5Y.KO	809	600	162
HRP 500.5Y.KO	809	600	162
HRP 1000.5Y.KO	1011	800	182
HRP 1500.5Y.KO	1250	1000	235
HRP 2000.5Y.KO	1250	1000	235

Dimensions in mm