



More information on the website
radwag.com/en/info,w1,TPE

MYA 0.8/3.5Y Microbalance



MYA 0.8/3.5Y Microbalance

The drawings, photos and graphics used are for illustrative purposes only.

Functions



Autotest



Dosing



Percent Weighing



Parts counting



Peak hold



Formulation



Newton unit
measurement



Statistics



Checkweighing



IR sensors



GLP Procedures



Animal weighing



Pipettes Calibration



Air density correction



Density determination



Moveable range



Differential weighing



Ambient conditions
monitoring



Statistical Quality Control



Packaged Goods Control



ALIBI Memory



Wi-Fi

Datasheet

	MYA 0.8/3.5Y Microbalance
Metrological parameters	
Maximum capacity [Max]	0,8/3 g
Minimum load	0,1 mg
Readability [d]	1/10 µg
Verification unit [e]	1 mg
Tare range	-3 g
Standard repeatability [5% Max]	0,6 µg
Standard repeatability [Max]	4,1 µg
Standard minimum weight (USP)	1,2 mg
Standard minimum weight (U=1%, k=2)	0,12 mg
Permissible repeatability [5% Max]	1,2 µg
Permissible repeatability [Max]	6 µg
Linearity	±3/10 µg
Eccentric load deviation	3/10 µg
Sensitivity time drift	$1 \times 10^{-6} / \text{Year} \times R_t$
Stabilization time	max 8 s
Adjustment	internal (automatic)
OIML Class	I
Physical parameters	
Leveling system	automatic - Reflex Level System
Display	10" touchscreen
Weighing chamber doors	automatic
Delivery components	Microbalance, terminal, weighing pan, weighing pan shield, glass lid, power supply, pincette, brush, fabric dust cover.
Weighing chamber dimensions	ø90×90 mm
Weighing pan dimensions	ø16 + ø60 mm
Packaging dimensions	750×492×595 mm
Net weight	9,1 kg
Gross weight	16,6 kg
Communication interface	
Communication interface	USB-A x2, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters	
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A; 15V DC 2,4A Balance: 12 – 15V DC 1,4A max*
Environmental conditions	
Operating temperature	+10 – +40 °C
Operating temperature change rate	±0,3°C/1h (±1°C/8h)
Relative humidity change rate	±1%/h (±4%/8h)

* The power supply can be connected to the socket on the back of the balance housing or to the terminal.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Extra payment for verification



Accessories

MediaBox
RFID Tags
Antivibration Tables
Power Adapters
Additional modules
Anti-Draft Chamber for Microbalances
Professional Weighing Tables
Protective cover for balances
Barcode scanners

RS 232, RS 485 cables
USB Hubs
RS 232, RS 485 cables
THBR 2.0 System - Ambient Conditions Monitoring
Weighing dishes
Receipt Printer
Fingerprint Reader
Protective cover for balances
RS 232 – USB Converter

Software

E2R System
Label Editor R02
R-LAB
RADWAG Development Studio

RAD-KEY
RADWAG Remote Desktop
Scales Editor 2.1

Device dimensions

MYA 0.8/3.5Y Microbalance

