



More information on the website
radwag.com/en/info,w1,Y10

SM-UYA 6.5Y.KO Susceptometer



The drawings, photos and graphics used are for illustrative purposes only.

Datasheet

Metrological parameters	
E1	2 g ÷ 50 kg
E2	2 g ÷ 50 kg
F1	2 g ÷ 50 kg
F2	2 g ÷ 50 kg
Maximum capacity [Max]	50 kg
Readability [d]	0,1 µg
Stabilization time	10 s
Adjustment	internal (automatic)
Calibration Range	2g÷50kg
Distance platform Z0	20; 27; 43 mm
Magnetizing field strenght	2000, 800, 200 A/m
Physical parameters	
Display	10" touchscreen
Weighing pan dimensions	ø300 mm
Device dimensions	525×350×250 mm

Physical parameters		
Packaging dimensions		950×750×750 mm
Net weight		26 kg
Gross weight		36 kg
Dipole moment of magnets		≤ 0,1 Am ²
Communication interface		
Communication interface		USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Environmental conditions		
Operating temperature		+15 ÷ +30 °C
Operating temperature change rate		±0,5°C/12h (±0,3°C/4h)
Relative humidity		40% ÷ 60%
Relative humidity change rate		± 2 % / 4 h
Construction		
Housing		ABS plastic
Components and software		
Processor		2×1 GHz
Memory		RAM 256 MB DDR2, 16GB - microSD

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories

Antivibration Tables
 Protective cover for balances
 THBR 2.0 System - Ambient Conditions Monitoring

Receipt Printer
 Fingerprint Reader

Software

RMCS System

THB-R