



More information on the website
radwag.com/en/info,w1,MIA

UYA 2.5Y.F Ultra-Microbalance



The drawings, photos and graphics used are for illustrative purposes only.

Functions

-  Autotest
-  Dosing
-  Percent Weighing
-  Parts counting
-  Peak hold
-  Formulation
-  Newton unit measurement
-  Statistics
-  Checkweighing
-  IR sensors
-  GLP Procedures
-  Animal weighing
-  Pipettes Calibration
-  Air density correction
-  Density determination
-  Differential weighing
-  Ambient conditions monitoring
-  Statistical Quality Control
-  Packaged Goods Control
-  ALIBI Memory
-  Wi-Fi

Datasheet

Metrological parameters

Maximum capacity [Max]	2.1 g
Minimum load	0.01 mg

Metrological parameters	
Readability [d]	0.1 µg
Verification unit [e]	1 mg
Tare range	-2.1 g
Standard repeatability [5% Max]	0.15 µg
Standard repeatability [Max]	0.35 µg
Standard minimum weight (USP)	0.3 mg
Standard minimum weight (U=1%, k=2)	0.03 mg
Permissible repeatability [5% Max]	0.35 µg
Permissible repeatability [Max]	0.6 µg
Linearity	±1.5 µg
Eccentric load deviation	1.5 µg
Sensitivity time drift	1×10 ⁻⁶ /Year×Rt
Stabilization time	10 - 20 s
Adjustment	internal (automatic)
OIML Class	I
Physical parameters	
Leveling system	automatic - Reflex Level System
Display	10" touchscreen
Delivery components	Ultra-microbalance, terminal, weighing pan, weighing pan for filters, centring ring, glass lid, pincette, brush, fabric dust cover.
Weighing chamber dimensions	Ø 93.8×35 mm
Weighing pan dimensions	Ø70 + Ø16 mm
Packaging dimensions	750×492×595 mm
Net weight	9.1 kg
Gross weight	16.5 kg
Communication interface	
Communication interface	USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters	
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A; 15V DC 2.4A Balance: 12 – 15V DC 1.4A max*
Environmental conditions	
Operating temperature	+10 – +40 °C
Operating temperature change rate	±0.3°C/1h (±1°C/8h)
Relative humidity change rate	±1%/h (±4%/8h)
Relative humidity	40% – 80%

* The power supply can be connected to the socket on the back of the balance housing or to the terminal.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Extra payment for verification



Accessories

MediaBox

RFID Tags

Antivibration Tables

Power Adapters

Additional modules

Professional Weighing Tables

Protective cover for balances

Barcode scanners

RS 232, RS 485 cables

Label Printers

RS 232, RS 485 cables

THBR 2.0 System - Ambient Conditions Monitoring

Receipt Printer

Fingerprint Reader

Software

• E2R Weighing [WX-010-0099]

• RAD Key [WX-010-0005]

• RADWAG Remote Desktop [WX-010-0107]

• Scale Editor 2.1 [WX-010-0173]

• E2R Weighing Records [WX-010-0038]

• Label Editor R02 [WX-010-0094]

• R-Lab [WX-010-0080]

• RADWAG Development Studio [WX-010-0104]

Device dimensions

