



More information on the website  
[radwag.com/en/info,w1,LKD](http://radwag.com/en/info,w1,LKD)

**XA 310.5Y Analytical Balance**



XA 310.5Y Analytical Balance

The drawings, photos and graphics used are for illustrative purposes only.

## Functions



Autotest



Dosing



Percent Weighing



Parts counting



Peak hold



Formulation



Newton unit measurement



Statistics



Checkweighing



IR sensors



Under-pan weighing



GLP Procedures



Animal weighing



Pipettes Calibration



Air density correction



Density determination



Differential weighing



Ambient conditions monitoring



Statistical Quality Control



Packaged Goods Control



ALIBI Memory



Wi-Fi

# Datasheet

	XA 310.5Y Analytical Balance
<b>Metrological parameters</b>	
Maximum capacity [Max]	310 g
Minimum load	10 mg
Readability [d]	0,1 mg
Verification unit [e]	1 mg
Tare range	-310 g
Standard repeatability [5% Max]	0,05 mg
Standard repeatability [Max]	0,1 mg
Standard minimum weight (USP)	100 mg
Standard minimum weight (U=1%, k=2)	10 mg
Permissible repeatability [5% Max]	0,07 mg
Permissible repeatability [Max]	0,15 mg
Linearity	±0,2 mg
Eccentric load deviation	0,3 mg
Sensitivity time drift	1×10 <sup>-6</sup> /Year×Rt
Stabilization time	1,3 s
Adjustment	internal (automatic)
OIML Class	I
<b>Physical parameters</b>	
Leveling system	semi-automatic - LevelSENSING
Display	10" touchscreen
Weighing chamber doors	manual
Delivery components	Analytical Balance, weighing pan, weighing pan shield, bottom cover, brush, fabric dust cover, power supply.
Weighing chamber dimensions	168×160×228 mm
Weighing pan dimensions	ø100 mm
Packaging dimensions	750×492×595 mm
Net weight	9,8 kg
Gross weight	14,3 kg
<b>Construction</b>	
Protection class	IP 43
<b>Communication interface</b>	
Communication interface	USB-A ×2, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
<b>Electrical parameters</b>	
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A; 15V DC 2,4A Balance: 12 – 15V DC 1,6A max*
<b>Environmental conditions</b>	
Operating temperature	+10 – +40 °C
Operating temperature change rate	±0,3°C/1h (±1°C/8h)
Relative humidity change rate	±1%/h (±4%/8h)

\* The power supply can be connected to the socket on the back of the balance housing or to the terminal.

\* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Extra payment for verification



## Accessories

MediaBox  
RFID Tags  
Antivibration Tables  
Power Adapters  
RS 232, RS 485 cables  
Holders for laboratory flasks  
Density determination KIT  
Additional modules  
Holders for test tubes and filters  
Professional Weighing Tables  
Protective cover for balances  
Barcode scanners  
Automatic feeders

USB Hubs  
Label Printers  
RS 232, RS 485 cables  
THBR 2.0 System - Ambient Conditions Monitoring  
Protective cover for balances  
Under-pan weighing  
Anti-Draft Chamber for XA 4Y and XA 5Y Balances  
Weighing dishes  
Receipt Printer  
Fingerprint Reader  
RS 232 – USB Converter  
Under-pan weighing

## Software

E2R System  
Label Editor R02  
R-LAB  
RADWAG Development Studio

RAD-KEY  
RADWAG Remote Desktop  
Scales Editor 2.1

## Device dimensions

XA 310.5Y Analytical Balance

