



More information on the website
radwag.com/en/info,w1,K7E

XA 6.5Y.M Microbalance



XA 6.5Y.M Microbalance

The drawings, photos and graphics used are for illustrative purposes only.

Functions



Autotest



Dosing



Percent Weighing



Parts counting



Peak hold



Formulation



Newton unit
measurement



Statistics



Checkweighing



IR sensors



GLP Procedures



Animal weighing



Pipettes Calibration



Air density correction



Density determination



Differential weighing



Ambient conditions
monitoring



Statistical Quality Control



Packaged Goods Control



ALIBI Memory



Wi-Fi

Datasheet

	XA 6.5Y.M Microbalance
Metrological parameters	
Maximum capacity [Max]	6,1 g
Minimum load	0,1 mg
Readability [d]	1 µg
Verification scale interval [e]	1 mg
Tare range	-6,1 g
Standard repeatability [5% Max]	0,8 µg
Standard repeatability [Max]	2,5 µg
Standard minimum weight (USP)	1,6 mg
Standard minimum weight (U=1%, k=2)	0,16 mg
Permissible repeatability [5% Max]	1,5 µg
Permissible repeatability [Max]	3 µg
Linearity	±7 µg
Eccentric load deviation	7 µg
Sensitivity time drift	$1 \times 10^{-6} / \text{Year} \times R_t$
Stabilization time	~3,5 s
Adjustment	internal (automatic)
OIML Class	I
Physical parameters	
Leveling system	semi-automatic - LevelSENSING
Display	10" touchscreen
Delivery components	Microbalance, weighing pan, weighing pan shield, bottom cover, power supply, brush, fabric dust cover.
Weighing chamber dimensions	168×160×228 mm
Weighing pan dimensions	ø30 mm
Packaging dimensions	435 x 885 x 540 mm
Net weight	9,8 kg
Gross weight	14,3 kg
Communication interface	
Communication interface	USB-A x2, USB-C, HDMI, Ethernet, Wi-Fi, Hotspot
Electrical parameters	
Power supply	Adapter: 100 – 240V AC 50/60Hz 1A; 15V DC 2,4A Balance: 12 – 15V DC 1,4A max*
Environmental conditions	
Operating temperature	+10 – +40 °C
Operating temperature change rate	±0,3°C/1h (±1°C/8h)
Relative humidity	40% – 80%
Relative humidity change rate	±1%/h (±4%/8h)

* The power supply can be connected to the socket on the back of the balance housing or to the terminal.

* Wi-Fi® is a registered trademark of Wi-Fi® Alliance.



Accessories

Barcode scanners
Professional weighing table
MICRO-KIT - Set of Holders for Microscale Glassware
USB Hubs
Label Printers
THBR 2.0 System - Ambient Conditions Monitoring

Anti-Draft Chamber for XA 4Y and XA 5Y Balances
Weighing dishes
Fingerprint Reader
RS 232 – USB Converter
RS 232, RS 485 cables

Software

RAD-KEY
LabVIEW Driver
RADWAG Remote Desktop
Scales Editor 2.1
R.Barcode

Audit Trail Reader
Label Editor R02
R-LAB
RADWAG Development Studio

Device dimensions

XA 6.5Y.M Microbalance

